

## TENSION-RESISTANT CONNECTION BETWEEN A SHIELDED HEATING CABLE AND A POWER SUPPLY CABLE

5

### FIELD OF THE INVENTION

**[0001]** The present invention relates to a tension-resistant electrical and mechanical connection between multi-conductor cables.

10

### BACKGROUND OF THE INVENTION

**[0002]** United States patent No. 2,452,823 granted to Wright on November 15 2<sup>nd</sup>, 1948 describes a splice between free ends of two shielded cables. More specifically, the two cables each comprise multiple current-carrying conductors enclosed within a wire braid.

**[0003]** The cable splice of Wright requires stripping of the insulation from the 20 free ends of the conductors. Each pair of conductors from the two cables are connected by means of a splicing tube and then individually insulated. A braided wire sleeve is then drawn over the spliced portion of the conductors. The sleeve is then extended longitudinally to cause it to engage the splice, and is then lashed firmly in place with a lashing wire. Finally, the sleeve is securely 25 lashed to portions of the wire braids and connects them mechanically.

**[0004]** The cable splice of United States patent No. 2,452,823 is not only complex but does not allow the wire braids of the two cables to efficiently and totally support a longitudinal tension applied to the cable splice.

30

## SUMMARY OF THE INVENTION

**[0005]** The present invention relates to a method of electrically and mechanically connecting (a) a first shielded cable comprising a metal sheath and electrical conductors with (b) a second cable comprising a ground conductor and electrical conductors. The method comprises:

- connecting, in a zone of interconnection between the first and second cables, a free end of the metal sheath with a free end of the ground conductor;
- connecting, in the interconnection zone, free ends of the electrical conductors of the first cable with free ends of the electrical conductors of the second cable, respectively; and
- making, in the interconnection zone, a length of the interconnected metal sheath and ground conductor shorter than lengths of the interconnected electrical conductors of the first cable and electrical conductors of the second cable whereby, in operation, longitudinal tension in the interconnection zone is totally supported by the interconnected metal sheath and ground conductor.

**[0006]** The present invention also relates to an electrical and mechanical connection between (a) a first shielded cable comprising a metal sheath and electrical conductors and (b) a second cable comprising a ground conductor and electrical conductors. The electrical and mechanical connection comprises:

- a zone of interconnection between the first and second cables;
- in the interconnection zone, a first connection between a free end of the metal sheath and a free end of the ground conductor; and
- in the interconnection zone, second connections between free ends of the electrical conductors of the first cable and free ends of the electrical conductors of the second cable, respectively;
- wherein, in the interconnection zone, the interconnected metal sheath and ground conductor have a first length shorter than second lengths of the interconnected electrical conductors of the first cable and electrical conductors of the second cable whereby, in operation, longitudinal tension in the

interconnection zone is totally supported by the interconnected metal sheath and ground conductor.

**[0007]** The present invention further relates to a method of electrically and mechanically connecting (a) a shielded heating cable comprising a metal sheath and heating wire elements with (b) a power supply cable comprising a ground conductor and power supply conductors. The method comprises:

connecting, in a zone of interconnection between the shielded heating cable and the power supply cable, a free end of the metal sheath with a free end of the ground conductor;

connecting, in the interconnection zone, free ends of the heating wire elements with free ends of the power supply conductors, respectively; and

making, in the interconnection zone, a length of the interconnected metal sheath and ground conductor shorter than lengths of the interconnected heating wire elements and power supply conductors whereby, in operation, longitudinal tension in the interconnection zone is totally supported by the interconnected metal sheath and ground conductor.

**[0008]** The present invention still further relates to an electrical and mechanical connection between (a) a shielded heating cable comprising a metal sheath and heating wire elements and (b) a power supply cable comprising a ground conductor and power supply conductors. The electrical and mechanical connection comprises:

a zone of interconnection between the shielded heating cable and the power supply cable;

in the interconnection zone, a first connection between a free end of the metal sheath and a free end of the ground conductor; and

in the interconnection zone, second connections between free ends of the heating wire elements and free ends of the power supply conductors, respectively;

wherein, in the interconnection zone, the interconnected metal sheath and ground conductor have a first length shorter than second lengths of the

interconnected heating wire elements and power supply conductors whereby, in operation, longitudinal tension in the interconnection zone is totally supported by the interconnected metal sheath and ground conductor.

- 5   **[0009]** The foregoing and other objects, advantages and features of the present invention will become more apparent upon reading of the following non-restrictive description of illustrative embodiments thereof, given by way of example only with reference to the accompanying drawings.

10

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the appended drawings:

- 15   **[0010]** Figure 1 is a side elevational view of a non-restrictive illustrative embodiment of the present invention, showing an interconnection zone between a shielded heating cable and a power supply cable.

20

#### DETAILED DESCRIPTION OF THE ILLUSTRATIVE EMBODIMENT

- [0011]** The non-restrictive illustrative embodiment of the method and connection according to the present invention, for electrically and mechanically connecting a shielded heating cable with a power supply cable will now be  
25   described with reference to Figure 1.

- [0012]** Although the present invention will be described in relation to connection of a shielded heating cable with a power supply cable, it should be kept in mind that it is within the scope of the present invention to apply the  
30   same concept to other types of multi-conductor cables.

*Shielded heating cable 1*

**[0013]** Referring to Figure 1, the shielded heating cable, generally identified by the reference 1 comprises:

- 5       - a pair of spirally twisted heating wire elements 11 and 12;
- a metal sheath 13 enclosing the pair of spirally twisted heating wire elements 11 and 12; and
- an insulating jacket 14 covering the metal sheath 13.

10       *Heating wire element 11*

**[0014]** The heating wire element 11 comprises a resistance wire 111 covered with insulation 112.

- 15       **[0015]** The resistance wire 111 has an electrical resistance (resistance by unit of length of resistance wire) dependent on the diameter of the wire 111. More specifically, the electrical resistance of the resistance wire 111 is adjusted, taking into consideration the total length of the heating wire element 11 in a typical installation, to release a given amount of heat when supplied with
- 20       alternating current from, for example, a 120-Volt 60-Hz voltage source commonly found in residential, industrial and commercial buildings.

- [0016]** The resistance wire 111 can be made of copper, or another electrically conductive material, for example an electrically conductive metal other than
- 25       copper, or an electrically conductive metal alloy including copper and/or any other suitable metal(s).

- [0017]** The insulation 112 of the heating wire element 11 can be made of extruded plastic material such as polyethylene or polypropylene capable of
- 30       withstanding and conducting the heat generated by and released from the resistance wire 111.

*Heating wire element 12*

**[0018]** In the same manner, the heating wire element 12 comprises a resistance wire 121 covered with insulation 122.

5

**[0019]** The resistance wire 121 has an electrical resistance (resistance by unit of length of resistance wire) dependent on the diameter of the wire 121. More specifically, the electrical resistance of the resistance wire 121 is adjusted, taking into consideration the total length of the heating wire element 12 in a typical installation, to release a given amount of heat when supplied with alternating current from, for example, a 120-Volt 60-Hz voltage source commonly found in residential, industrial and commercial buildings.

**[0020]** The resistance wire 121 can be made of copper, or another electrically conductive material, for example an electrically conductive metal other than copper, or an electrically conductive metal alloy including copper and/or any other suitable metal(s).

**[0021]** The insulation 122 of the heating wire element 12 can be made of extruded plastic material such as polyethylene or polypropylene capable of withstanding and conducting the heat generated by and released from the resistance wire 121.

**[0022]** The heating wire elements 11 and 12 are spirally twisted with a given lay, this lay corresponding to the length required by the heating wire elements 11 and 12 to be spirally twisted by 1 turn. An advantage is that, by spirally twisting the heating wire elements 11 and 12, the electromagnetic field from the heating wire element 11 and the electromagnetic field from the heating wire element 12 substantially cancel each other, of course when the current has the same given amplitude in the two heating wire elements 11 and 12, and the current flowing through the heating wire element 11 flows in a direction opposite to the current flowing through the heating wire element 12.

### *Metal sheath 13*

5     **[0023]** The metal sheath 13 is formed of a plurality of small-diameter copper wires braided together to form a tubular shielding and/or a metal tape spirally wound or longitudinally applied. The main function of the metal sheath 13 is to ground the heating cable 1 through a connection to the ground. The metal sheath 13 is also designed to resist to impacts as strong as 100 lbs.

10    **[0024]** Of course, the metal sheath 13 will comprise braided wires and/or tape made of an electrically conductive material capable of withstanding and conducting the heat generated by and released from the resistance wires 111 and 121. Although this material could be copper, it is within the scope of the present invention to use another electrically conductive material, for example  
15    an electrically conductive metal other than copper, or an electrically conductive metal alloy including copper and/or any other suitable metal(s).

### *Insulating jacket 14*

20    **[0025]** The insulating jacket 14 covering the metal sheath 13 can be made of extruded plastic or elastomeric material with or without subsequent cross-linking such as polyethylene or polypropylene capable of withstanding and conducting the heat generated by and released from the resistance wires 111 and 121.

25

### *Power supply cable 2*

**[0026]** Still referring to Figure 1, the power supply cable, generally identified by the reference 2, comprises:

- 30     - an insulated ground conductor 22;  
      - two insulated electrical conductors 21 and 23; and  
      - an insulating jacket 24 enclosing the three insulated conductors 21, 22

and 23.

*Insulated electrical conductor 21*

- 5   **[0027]** The insulated electrical conductor 21 comprises an electrically  
conductive wire 211 covered with insulation 212. The electrically conductive  
wire 211 can be made of copper, or of another electrically conductive material,  
for example an electrically conductive metal other than copper, or an  
electrically conductive metal alloy including copper and/or any other suitable  
10 metal(s). The insulation 212 of the insulated electrical conductor 21 can be  
made of extruded plastic material such as polyethylene or polypropylene.

*Insulated ground conductor 22*

- 15   **[0028]** The insulated ground conductor 22 comprises an electrically conductive  
wire 221 covered with insulation 222. The electrically conductive wire 221 can  
be made of copper, or of another electrically conductive material, for example  
an electrically conductive metal other than copper, or an electrically conductive  
metal alloy including copper and/or any other suitable metal(s). The insulation  
20 222 of the insulated ground conductor 22 can be made of extruded plastic  
material such as polyethylene or polypropylene.

*Insulated electrical conductor 23*

- 25   **[0029]** The insulated electrical conductor 23 comprises an electrically  
conductive wire 231 covered with insulation 232. This electrically conductive  
wire 231 can be made of copper, or of another electrically conductive material,  
for example an electrically conductive metal other than copper, or an  
electrically conductive metal alloy including copper and/or any other suitable  
30 metal(s). The insulation 232 of the insulated electrical conductor 23 can be  
made of extruded plastic material such as polyethylene or polypropylene.



*Insulating jacket 24*

**[0030]** The insulating jacket 24 enclosing the three insulated conductors 21-23 can be made of extruded plastic or elastomeric material with or without  
5 subsequent cross-linking such as polyethylene or polypropylene.

*Electrical and mechanical connection*

**[0031]** To electrically and mechanically connect a free end 15 of the shielded  
10 heating cable 1 to a free end 25 of the power supply cable 2, the following operations are conducted:

- the insulating jacket 14 is stripped from the free end 15 of the shielded heating cable 1 to expose a free end of the metal sheath 13;  
15
- the heating wire elements 11 and 12 are withdrawn from the exposed free end of the metal sheath 13;
- the insulation 112 is stripped from the free end of the heating wire element  
20 11 to expose a free end 113 of the resistance wire 111;
- the insulation 122 is stripped from the free end of the heating wire element  
25 12 to expose a free end 123 of the resistance wire 121;
- the insulation 212 is stripped from the free end of the power supply conductor 21 to exposed a free end 213 of the electrically conductive wire 211;
- the insulation 222 is stripped from the free end of the ground conductor 22  
30 to exposed a free end 223 of the electrically conductive wire 221;
- the insulation 232 is stripped from the free end of the power supply

conductor 23 to expose a free end 233 of the electrically conductive wire 231;

- the free end 223 of the electrically conductive wire 221 of the ground conductor 22 is ultrasonically welded to the free end of the metal sheath 13 corresponding to the stripped free end 15 of the shielded heating cable;
- the free ends 113 and 213 are ultrasonically welded; and
- the free ends 123 and 233 are ultrasonically welded.

**[0032]** As illustrated in Figure 1, in a zone 3 of interconnection between the shielded heating cable 1 and the power supply cable 2, the interconnected metal sheath 13 and ground conductor 22 have a length shorter than a length of the interconnected heating wire element 11 and power supply conductor 21. Also, the interconnected metal sheath 13 and ground conductor 22 have, in the zone 3, a length shorter than a length of the interconnected heating wire element 12 and power supply conductor 23. In this manner, in operation, longitudinal tension in the interconnection zone 3 is totally supported by the interconnected metal sheath 13 and ground conductor 22.

**[0033]** Since the heating wire elements 11 and 12 have small-diameter, fragile resistance wires 111 and 121, the construction illustrated in Figure 1 will protect the resistance wires 111 and 121 from rupture or other damage caused by tension in the interconnection zone 3 of the cables 1 and 2.

**[0034]** The loop made with each of the resistance wires 111 and 121 at the point of connection between the shielded heating cable 1 and the power supply cable 2 also provides room to relieve the stress caused by the thermal expansion of the resistance wires 111 and 112 when electrical power is applied. The resistance wires 111 and 121 having a diameter much smaller than the electrically conductive wires 211 and 231 of the power supply cable 2

(non-heating cable), without these loops, all of the expansion stress would be localized at the weakest points of the resistance wires 111 and 121, which would be the points just next to the respective connections with the electrically conductive wires 211 and 231 of the power supply cable 2. Without the loops,  
5 there would be a higher probability of having power interruptions due to the breakage of the resistance wires 111 and 121 at these particular points.

**[0035]** Although the non-restrictive illustrative embodiment of the present invention has been described in relation to ultrasonic welding of the wires and  
10 sheath, it should be kept in mind that it is within the scope of the present invention to use other types of welding as well as other types of connections.

**[0036]** Also, the interconnected heating wire element 11 and power supply conductor 21 can form a 360° loop (not shown) in the interconnection zone 3.  
15 The free wire ends 113 and 213 can then be placed side by side in the continuity of both the heating wire element 11 and power supply conductor 21 and ultrasonically welded in this position.

**[0037]** In the same manner, the interconnected heating wire element 12 and  
20 power supply conductor 23 can form a 360° loop (not shown) in the interconnection zone 3. The free wire ends 123 and 233 can then be placed side by side in the continuity of both the heating wire element 12 and power supply conductor 23 and ultrasonically welded in this position.

**[0038]** Finally, the interconnected wire free end 223 and metal sheath free  
25 end, the interconnected free ends 113 and 213, and the interconnected free ends 123 and 233 are individually insulated using conventional techniques well known to those of ordinary skill in the art. In the same manner the individually insulated interconnected wire free end 223 and metal sheath free end,  
30 interconnected free ends 113 and 213, and interconnected free ends 123 and 233 are finally globally covered with additional insulation, for example a heat-shrinkable jacket covering the interconnection zone 3 and adjacent portions of

the insulating jackets 14 and 24.

**[0039]** Although the present invention has been described hereinabove by way of a non-restrictive illustrative embodiment thereof, this embodiment can be  
5 modified at will, within the scope of the appended claims, without departing from the spirit and scope of the present invention.